

## Panic Alert



EMERGENCY SITUATIONS > *Panic Alert* is a **LoadTrak™** feature that enables drivers to notify their company in an emergency situation.

### Lone worker? Safety and security with Panic Alert.

- The *Panic Alert* remote devices offer drivers increased safety, security and peace of mind.
- The *Panic Alert* devices are small enough to be carried on the driver at all times, so it will never be out of reach if the driver needs help.
- *Panic Alert* gives drivers access to a 24/7 monitoring centre at the push of a button or by choosing the sensor/man-down mode.
- *Panic Alert* is perfect for drivers travelling alone or working in remote locations.
- The *Panic Alert* devices have a 300-metre signal radius from the vehicle and real-time driver location information.
- *Panic Alert* is available either as a stand-alone product or an add-on option to the **LoadTrak** Vehicle Tracking solution.
- *Panic Alert* includes features such as the addition of the Legal Subdivision (LSD) location in the call out from the monitoring centre and Email Notification as a secondary method of notification.



In an emergency situation, a driver can press a button or in the event that the driver is immobile, an emergency signal will be sent through the **LoadTrak** device in the truck to the SecurTek monitoring centre. The monitoring centre will then contact the driver's company and indicate the precise location of the driver.

# Panic Alert Devices

## TPASS (TPASS 3 / TPASS LTX200 / TPASS 3-OR)

### PRODUCT DESCRIPTION:

Dimensions: 2"W, 3 1/8" H, 1 1/2" deep

Battery Type: 9 volt Duracell MN 1604 (included)

Weight: 8 oz. with battery

Battery Life (approximate): Sensing Mode: TPASS 3 and TPASS LTX200 - approximately 30 hours  
TPASS 3-OR - approximately 50 hours  
Alarm Mode: 2 – 4 hours



### PRODUCT FEATURES:

- **Intrinsically Safe:**  
Certified per ANSI/UL-913 for use in Class 1, Div. 1, Group A, B, C and D Hazardous Locations.
- **CSA Approved:**  
Certified to CAN/CSA Std. C22.2 No. 157-92.
- **Automatic Motion Sensing / Man-Down Alarm Activation:**  
The alarm is programmed to go off after a preset amount of time. Users select between four amounts of time ranging between 30 seconds and 120 seconds.  
  
A loud audio alarm will sound and an alarm signal will be sent to the SecurTek monitoring centre when the unit has been immobile for longer than the pre-determined amount of time.
- **Manual Mode Alarm Activation (Panic Button):**  
A Manual Push Button can be pressed to send an alarm signal to the SecurTek monitoring centre.
- **Confirmation that TPASS is active:**  
Visible Flashing LED lights indicates that the TPASS is active.
- **Low-Battery Alarm:**  
An alarm will sound when the battery is at 20% capacity (allowing for one hour operation in alarm mode).
- **Multiple-Users:**  
Available to allow multiple users to a single vehicle.
- **Automatic Activation – Tethered Accountability Key (Option):**  
The TPASS is automatically turned on when the proprietary tethered accountability key is removed.
- **Out-of-Range (Available with the TPASS 3-OR):**
  - The first Out-of-Range Notification occurs at approximately 3 minutes.
  - Out-of-Range reminder notifications occur approximately every 30 - 40 seconds while out of range.

## Key Fob

### PRODUCT DESCRIPTION:

Dimensions: 1 9/16"W, 2 3/4"H, 1/2" deep

Battery Type: Two CR2025 Button Cell Batteries

Battery Life (approximate): up to one year



### PRODUCT FEATURES:

- **Manual Mode Alarm Activation (Panic Button):**  
A Manual Push Button can be pressed to send an alarm signal to the SecurTek monitoring centre.
- **Multiple-Users:**  
Available to allow multiple users to a single vehicle.
- **Low-Battery Alarm:**  
When the battery is low, pressing any of the following buttons will result in all of them flashing to indicate a low battery: Lock, Unlock, Panic, Start.

For more information about the **LoadTrak** solution, or to locate an authorized **LoadTrak** dealer near you, visit [www.loadtrak.com](http://www.loadtrak.com) or call **1-866-LoadTrk** (1-866-562-3875).